



(11) **EP 1 398 174 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
17.03.2004 Bulletin 2004/12

(51) Int Cl.7: **B42D 15/00**

(21) Application number: **02405782.0**

(22) Date of filing: **10.09.2002**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
IE IT LI LU MC NL PT SE SK TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Moreau, Vincent**
1003 Lausanne (CH)

(74) Representative: **Kiliaridis, Constantin et al**
Bugnion S.A.,
10, Route de Florissant,
Case Postale 375
1211 Genève 12 (CH)

(71) Applicant: **KBA-GIORI S.A.**
1003 Lausanne (CH)

(54) **Reinforced substrate for securities**

(57) The note (1) comprises a substrate having a zone of reduced thickness (2) forming a transparent window in said substrate and reinforcing means (3) to increase the resistance of said zone (2).




Fig. 1

Description

[0001] The present invention concerns a note, such as a banknote, a security note or a check, comprising a substrate having a zone of reduced thickness forming a transparent window in said substrate.

[0002] The present invention also concerns a process for treating a substrate used for forming notes, such as banknotes and securities, having a transparent zone.

[0003] In the field of banknotes and securities, there has been increasing needs for safety features protecting against counterfeiting. Indeed, in the past years, computers, scanners and copy machines have been extensively developed and today, it is possible to buy very performant devices at a reasonable price. Since these devices are more performant, it has been at the same time necessary to develop new and improved safety features for securities, such as banknotes, checks, cards (i.e. credit cards), ID cards, passports etc. which would not allow them to be copied by standard computers or scanners, or even modern color copy machines.

[0004] Such safety features include special inks, so called optical variable inks (OVI), used to print specific patterns on the substrate of the note, optical variable devices (OVD) in the shape of metallized patches or holograms, or also specific patterns, such as moiré patterns and other similar patterns, all of which are very difficult if not impossible copy by actual devices, but, on the other hand, are easy to control visually.

[0005] Other safety means include combinations of superimposed lines and/or patterns with colors which are only visible under specific conditions, for example UV light or by transparency. Again, the interest of such safety means is that they may easily be printed or placed on the document to be protected and also be controlled by simple devices, even visually, but they are impossible to reproduce with actual printers, scanners or copy machines.

[0006] Another specific technique involves watermarks in which the paper substrate is marked with lines or patterns only visible in transparency. A further development of this technique concerns pseudo-watermarks consisting in the creation of a window in the substrate, especially in paper-based substrates which are normally not transparent, said window being transparent.

[0007] It is however very difficult to create or simulate a transparent window in a paper-based substrate. Transparent windows, as such, are widely used in polymer-based substrates for banknotes and securities, in order to provide a security element. These polymer based substrates are usually completely transparent, therefore, to form a transparent window, it is only necessary to leave the chosen zone free of printing. However, in the case of paper, a substrate which is not transparent, a first process has been developed according to which, it is possible to reduce locally the thickness of the paper in order to create a transparent window in the substrate. PCT application WO 99/14433 for example,

discloses this process and the content of this application is incorporated by reference in the present application. According to this known process, a soaking solution is applied on at least one surface of the paper in one or several predetermined zones, then one applies pressure and heat on the soaked zone so as to evaporate and densify the coated paper in said zone relative to the rest of the paper. Thus, said zones have a reduced thickness with respect to the rest of the paper and are transparent.

[0008] This first technique however has the drawback of weakening locally the paper in the zone comprising said window. In particular, the smaller the thickness of the window, the weaker the zone. Banknotes using such a technique thus have a reduced lifetime and must be exchanged, i.e. new bank notes must be printed to replace the older damaged ones.

[0009] Another technique implies to cut a hole directly in the paper in order to create the transparent window. For example, PCT application WO 95/10420, the content of which is incorporated by reference in the present application, discloses said other technique. It is of course necessary to cover the hole cut in the substrate, which is done in this case by covering the hole with a strip of transparent material, e.g. a foil or a laminate. This document specifically uses the contrast between the transparency of the window and a diffraction structure used as an additional security feature and placed inside the window. Modern copy machines and scanners are indeed unable to copy a diffraction structure and also a transparent window.

[0010] The aim of the invention is accordingly to improve the prior art.

[0011] More specifically, an object of the invention is to provide a safety feature for securities, such as banknotes, checks, ID or passports, which is very difficult to reproduce with modern printing, scanning and copying devices.

[0012] A further object of the invention is to provide a security document, such as banknotes, securities and other equivalent, comprising an improved safety feature.

[0013] The invention is defined according to the features of the claims.

[0014] An advantage of the invention is that it can be easily carried out with standard machines used in the field of producing banknotes.

[0015] Another advantage of the invention is that it provides a better support for adding further security features on the note, in particular directly on the zone with a reduced thickness, i.e. the transparent zone. One example of a safety feature which is particularly advantageous to use in the present application is disclosed in Swiss Patent application N°1661/01 filed on September 7, 2001 in the name of KBA-GIORI S.A., the content of this Swiss Patent application being incorporated by reference in the present application. The safety feature for printed matter described in this application comprises a

first drawing printed on one side of said printed matter, said drawing being made of a first set of geometrical shapes, and a second drawing printed on another side of the printed matter in register with a second set of geometrical shapes corresponding to the first set, but in which one of said sets comprises offset sectors so that when the recto-verso register is correct, the security feature forms zones of variable density that can be seen only in transparency.

[0016] In other words, only when the recto-verso register is correct is it possible to see the zones of variable density forming a specific shape, which has been determined by the offset sectors. The shape is usually a letter, a combination of alphanumerical characters (such as "OK") or another geometrical shape.

[0017] The first important fact is that said offset sectors are not visible to the naked eye. Therefore, a copy machine or a scanner is not able reproduce them and a note made with a color copy machine or a scanner will not have the security feature.

[0018] The second important fact is that this security feature allows also an easy control the recto-verso register of the printing either visually or with simple optical devices. If the register is perfect or within a certain tolerance, the presence of the specific shape can be controlled. If the register is out of a certain tolerance or very bad, the specific shape will be absent of the printed matter.

[0019] In this technique, one uses mainly a set of very thin lines (with a width between 10 μm and 500 μm) spaced between 5 μm to 1000 μm . The offset sectors are thus also of this order of size. It is therefore very important that the substrate on which the lines are printed has smooth surface in order to obtain a precise printing. This is of course not the case when the substrate is made of paper and the fact that the zone in which the security element is printed is a zone of reduced thickness makes it even worse because of the fragility of said zone.

[0020] For this reason, the invention allows combinations of safety features overcoming technical difficulties and also provides a new technical result by novel features mutually supporting their technical effects. The invention also overcomes a technical prejudice according to which it was not possible to print matter on a zone of reduced thickness because of its fragility.

[0021] The invention will be better understood by the description of several embodiments with the accompanying drawings in which:

Figure 1 shows a first embodiment of the invention.

Figure 2 shows a second embodiment of the invention.

Figure 3 shows a third embodiment of the present invention.

Figure 4 shows a fourth embodiment of the present invention.

Figure 5 shows, in a schematical manner, a sheet comprising a plurality of notes according to the invention.

[0022] A first embodiment of the invention is described with reference to figure 1. In this figure, a note 1, for example a banknote, is represented. Said note 1 has a given thickness and comprises a zone 2 of reduced thickness. The zone 2 is represented as a circular zone, however other shapes (square, triangular etc.) are possible. Over said zone of reduced thickness 2, a strip of transparent material 3 is placed to reinforce said zone 2. The strip of transparent material is made of an appropriate material, such as, but not limited to, Polyester (PET) or Polycarbonate (PC) films. Other materials known in the art are of course possible. The strip of material is attached to the note by conventional techniques known in the art, such as gluing or other equivalent methods known in the art.

[0023] As a variant to this embodiment, a second strip of transparent material 10 may be placed on the other side of the note 1. This second strip 10 is schematically represented in figure 1 by broken lines on each side of the strip 3. Of course, the second strip may be of the same size than strip 3, the broken lines being placed on each side of the strip 3 to be visible. The second strip 10 may also be smaller or larger than the strip 3.

[0024] A second embodiment is represented in figure 2. In this figure 2, as in figure 1, the note 1 comprises a zone 2 of reduced thickness. Over the zone 2, a patch 4, such as an OVD, has been deposited using the techniques known in the art. This patch 4 comprises a metallized layer, however, a part 5 of this layer has been demetallized, this part 5 corresponding approximately to the surface of the zone 2 of reduced thickness. The remaining surface 6 of the patch is still metallized. The strip carrying the OVD being transparent, the demetallized part 5 is also transparent whereas the remaining surface 6 reflects light. In the present embodiment, a further safety effect, impossible to reproduce with scanners and copy machines, is provided by the contrast between the transparent demetallized part 5 and the reflective part 6.

[0025] A third embodiment is represented in figure 3. In this figure the note 1 comprises a zone of reduced thickness 7 over which a strip 8 of transparent material has been deposited. This is similar to the embodiment represented in figure 1. A security element 9 is further printed on the strip 8 in the zone corresponding to the zone of reduced thickness 7 of the note. This security element corresponds to the one described with reference to Swiss Patent application N°1661/01 mentioned above in the present specification. This security element 9 comprises a second set of lines printed on the other side of the note, but not represented here for the sake

of simplicity. Reference is thus made to the entire specification of Swiss Patent application N°1661/01 incorporated in the present application for the description of the principle of said security element.

[0026] As mentioned, the reinforced substrate according to the invention is particularly suitable for use in combination with the security element 9, as described in the Swiss Patent Application N°1661/01 since the strips 3, 8, 10 and the demetallized patch 4 provide a smooth surface on which such security elements 9 may be printed.

[0027] A further embodiment of the invention is represented in figure 4. This embodiment combines several elements of the embodiments according to figure 1 to 3, and shows a note 1 comprising a zone of reduced thickness 2. Over this zone 2, a patch 11 has been attached, said patch 11 comprising a demetallized portion 12 and a metallized portion 13. This configuration is similar to the one represented in figure 2. Further, a strip 14 of transparent material has been applied on the other face of the note 1 with respect to the patch 11 (said strip being represented by broken lines), and a security element 15 is placed on the patch, in the demetallized zone 12 of the patch 11 which corresponds to the zone of reduced thickness 2 of the note. The safety feature 15 is of the type using the transparency of the zone in which it has been applied, for example the principle described in Swiss Patent application N°1661/01, also used in the embodiment of figure 3.

[0028] This embodiment combines numerous different techniques which are all difficult, if not impossible, to reproduce with modern copy machines and scanners. It uses a substrate comprising a zone of reduced thickness, a partial optical device, a transparent window in which there is a further security element, the surface for this security element being very smooth (strip supporting the patch 11 and strip 14), thus improving the quality of the security element.

[0029] Of course, other security features/elements using the transparency of the substrate on which they are printed or applied may be used, and the embodiments described are only illustrating, by way of examples, the features of the invention.

[0030] Figure 5 shows in a schematical manner, a sheet, for example a paper sheet, comprising several notes according to the invention. The sheet 16, only partially represented for the sake of simplicity, comprises a plurality of notes placed in successive rows and columns, as it is done in a known fashion for banknotes. Each note 17, in the two first columns, comprises a zone of reduced thickness 18, which has been produced for example according to the process disclosed in PCT application WO 99/14433 (cited above and incorporated by reference). Further, a strip of transparent material 19 has been deposited on each note 17, either on one side of the sheet 16 (embodiment of figure 1), or on both sides (variant to the embodiment of figure 1).

[0031] In the fourth column, the notes 17 have re-

ceived a partially demetallized patch 20, this corresponding to the second embodiment shown in figure 2.

[0032] In the fifth column, the notes 17 are in the embodiment disclosed in figure 4 in which, on one side of the sheet 16, a partially demetallized patch 21 and on the other side of the sheet, a strip of transparent material 22 has been applied.

[0033] In the sixth column, the notes 17 have received an additional security element 23, similar to the one described here above, which can be placed in any note of the sheet, as has been described in the different embodiments of the invention.

[0034] Of course, this representation of several different embodiments is only given as an example, and normally, different embodiments of the invention would not be combined on the same sheet. Rather, depending on the complexity of the note and on the security features chosen, a particular embodiment would be selected and then all sheets would receive the proper treatment: strip on one side or both, patch on one side or both, or even in combination, with or without an additional security element as described here above.

[0035] In the present description, reference has been made mainly to banknotes, however, the principle of the invention is applicable to other similar documents (pages of passports, checks etc.) all of which comprise a non-transparent substrate in which a transparent zone has been created.

Claims

1. A note (1,17) such as a banknote or security note, said note (1,17) comprising a substrate having a zone of reduced thickness (2,7,18) forming a transparent window in said substrate, **characterised in that** the note further comprises reinforcing means (3,4,8,10,11,14,19,20,22) to increase the resistance of said zone.
2. A note as claimed in claim 1, **characterised in that** said substrate is made of a paper substrate.
3. A note as claimed in claim 1 or 2, **characterised in that** said reinforcing means comprise at least a strip of material (3,8,10,14,19) covering at least said zone of reduced thickness on at least one side of said substrate.
4. A note as claimed in claim 3, **characterised in that** said strip of material is a transparent polymer material.
5. A note as claimed in claim 1 or 2, **characterised in that** said reinforcing means comprise a patch (4,11,20,22) of material covering at least said zone of reduced thickness, said patch being formed by a partially demetallized OVD patch placed on at least

one side of said note.

6. A note as claimed in one of the preceding claims, **characterised in that** said reinforcing means further comprise an additional security feature (9,15,23). 5
7. A note as claimed in one of the preceding claims, **characterised in that** said reinforcing means (9,15,23) are placed on both sides of said note. 10
8. A note as claimed in one of claims 3 to 7, **characterised in that** said reinforcing means comprise a strip (14) on one side of said substrate and a patch (11) on the other side of said substrate. 15
9. A sheet of substrate (16) **characterised by** a plurality of notes as defined in any of claims 1 to 8.
10. Process for producing notes, such as banknotes or security notes, said notes comprising a substrate having a zone of reduced thickness forming a transparent window in said substrate, said process being **characterised by** the step of covering at least said zone on at least one side of said substrate with reinforcing means. 20 25
11. Process according to claim 10, **characterised in that** it comprises the step of covering said zone with reinforcing means on both sides of said substrate. 30
12. Process according to claim 11, **characterised in that** said reinforcing means comprise at least a strip or a patch of material. 35
13. Process according to one of claims 10 to 12, **characterised in that** it further comprises the step of providing said reinforcing means with an additional security feature. 40

45

50

55




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 40 5782

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	WO 95 10419 A (OESTERREICHISCHES NATIONALBANK) 20 April 1995 (1995-04-20) * the whole document *	1,10	B42D15/00
A	FR 2 767 091 A (MEYER JEAN CLAUDE) 12 February 1999 (1999-02-12) * the whole document *	1,10	
A	US 5 393 099 A (AMERICAN BANK NOTE HOLOGRAPHICS) 28 February 1995 (1995-02-28) * the whole document *	1,10	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			B42D
Place of search		Date of completion of the search	Examiner
THE HAGUE		17 February 2003	Loncke, J
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 40 5782

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

17-02-2003

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9510419 A	20-04-1995	AT 401365 B	26-08-1996
		AT 204493 A	15-01-1996
		WO 9510419 A1	20-04-1995
		AT 155743 T	15-08-1997
		DE 59403480 D1	04-09-1997
		DK 724519 T3	23-02-1998
		EP 0724519 A1	07-08-1996
		ES 2107859 T3	01-12-1997
		GR 3024985 T3	30-01-1998
		JP 9503460 T	08-04-1997
		SI 724519 T1	28-02-1998

FR 2767091 A	12-02-1999	FR 2767091 A1	12-02-1999

US 5393099 A	28-02-1995	NONE	
